



Product Range :

ID (m/m)	Part No	P / Std	Spool	Box	Recommended Cable Size (mm ²)
2.0	MS2020	200 M	●	●	(0.24-0.5)MM ² /(7/0.2)/AWG24
2.5	MS2520	200 M	●	●	(0.5-0.75)MM ² /AWG20/AWG22
3.0	MS3020	200 M	●	●	1.00MM ² /23/0076"/AWG18
3.2	MS3220	200 M	●	●	1.0-1.5MM ² /40/0076"/AWG16
3.5	MS3520	200 M	●	●	1.5MM ² /70/0076"/AWG16
3.6	MS3620	200 M	●	●	1.5MM ² /70/0076"/AWG14
4.0	MS4020	200 M	●	●	2.5MM ² /AWG14
4.2	MS4220	200 M	●	●	2.5MM ² /AWG14
4.5	MS4520	200 M	●	●	4.0MM ² /AWG12
5.0	MS5020	200 M	●	●	4.0-6.0MM ² /AWG10
5.2	MS5220	200 M	●	●	4.0-6.0MM ² /AWG10
5.5	MS5520	200 M	●	●	6.0MM ² /AWG10
6.0	MS6020	200 M	●	100 M	10.0MM ² /AWG8
6.5	MS6510	100 M	●	100 M	10.0MM ² /AWG8
7.0	MS7010	100 M	●	80 M	16.0MM ² /AWG6
8.0	MS8010	100 M	●	80 M	16.0MM ² /AWG6
10.0	MS1010	100 M	●	50 M	25.0MM ² /AWG4

Product Specification :

- Full range of tubes size ranging from 2.0 ~ 10.0m/m.
- Supplying in both Spool & Box type.
- Full range of colour available : White, Red, Blue, Yellow, Green, Black and Transparent.
Others colour & sizes available upon request.
- ROHS Compliances environmental friendly.
- Flame Retardant 94-V2 quality tubes is available on demand basic.

For further enquiry, kindly contact :

MATERIAL SPECIFICATION SHEET

Sample Analysis : Polyvinyl Chloride (PVC) Compound

Material Code : D11 F3

Colour : White, Yellow, Green, Blue, Black & Red

<i>Items</i>	<i>Test Method</i>	<i>Unit</i>	<i>Specification</i>
Tensile Strength At Yield	ASTM D 638	Mpa	13.8
Elongation At Yield	ASTM D 638	%	329
Colour	Visual	N/A	As Approved
Hardness	ASTM D2240-97	Shore A	85±5
Appearance	Visual	N/A	No abnormal appearance