



Larger sizes for big solutions
大型号产品提供大尺寸的解决方案



IP66/IP68/IP69

GGV flange, straight

In railway vehicle construction as well as in a wide range of industrial applications with high sealing and safety requirements.

GGV 法兰, 直型

在铁路车辆制造和不同工业应用中对高密封和安全要求的应用。



Order No. black 订货号 黑色	Fits to conduit size		Dimensions width 尺寸 宽	Dimensions height 尺寸 高	Dimensions depth 尺寸 深
	NW	metric			
BGGV-56	56	68	82.0	97.0	42.0
BGGV-70	70	80	97.0	114.0	48.0
BGGV-95	95	106	126.0	146.0	53.0

For technical specification in details, please ask for "Technical Data Sheet" DB-Nr.37005
要了解详细技术规格, 请索取“技术数据表”DB-Nr.37005

unit = mm
单位 = mm



- High-grade, specially formulated polyamide 6
- Flange seal FG04 made from EPDM
- Flange seal FG04 / 01 made from NBR on special request
- Very high impact strength
- Vibration-proof connection to PMAFLEX conduits
- High conduit pull-out strength
- Ingress protection: IP68, IP69
- Very good chemical properties
- Free from halogens and cadmium
- Temperature range: -40°C to +105°C
- Content of delivery: Flange part, fixation clamps (including 2 screws), conduit seal (NVN3), flange seal (FG04 or FG04 / 01)
- If the application temperature is above 70°C we recommend to use an additional internal conduit support sleeve (BES)

- 高级, 特殊配方聚酰胺6制成
- 法兰密封圈FG04由EPDM制成
- 按特殊要求可提供由NBR制造的法兰密封圈FG04 / 01
- 非常高的抗冲击强度
- 配合PMAFLEX软管使用具有很好的防震作用
- 高强度的抗拉能力
- 防护等级: IP68, IP69
- 非常好的化学性能
- 不含卤素和镉
- 温度范围: -40°C 至 +105°C
- 包装配件: 法兰主体, 固定夹 (包含两螺丝), 软管密封圈 (NVN3), 法兰密封圈 (FG04 或 FG04 / 01)
- 如应用温度高于70°C, 我们推荐使用附件, 软管内套支撑 (BES), 维持长时间的密封性能。

IP66/IP68/IP69

GOV flange, 90° elbow

In railway vehicle construction as well as in a wide range of industrial applications with high sealing and safety requirements.

GOV 法兰, 90°弯头

在铁路车辆制造和不同工业应用中对高密封和安全要求的应用。



Order No. black 订货号 黑色	Fits to conduit size		Dimensions width 尺寸 宽	Dimensions height 尺寸 高	Dimensions depth 尺寸 深
	NW	metric			
BGOV-56	56	68	82.0	97.0	101.0
BGOV-70	70	80	97.0	114.0	115.0
BGOV-95	95	106	126.0	146.0	149.0

For technical specification in details, please ask for "Technical Data Sheet" DB-Nr.37015
要了解详细技术规格, 请索取“技术数据表”DB-Nr.37015

unit = mm
单位 = mm



- High-grade, specially formulated polyamide 6
- Flange seal FG04 made from EPDM
- Flange seal FG04 / 01 made from NBR on special request
- Very high impact strength
- Vibration-proof connection to PMAFLEX conduits
- High conduit pull-out strength
- Ingress protection: IP68, IP69
- Very good chemical properties
- Free from halogens and cadmium
- Temperature range: -40°C to +105°C;
- Content of delivery: Flange part, fixation clamps (including 2 screws), conduit seal (NVN3), flange seal (FG04 or FG04/01)
- If the application temperature is above 70°C we recommend to use an additional internal conduit support sleeve (BES)

- 高级, 特殊配方聚酰胺6制成
- 法兰密封圈FG04由EPDM制成
- 按特殊要求可提供由NBR制造的法兰密封圈FG04 / 01
- 非常高的抗冲击强度
- 配合PMAFLEX软管使用具有很好的防震作用
- 高强度的抗拉能力
- 防护等级: IP68, IP69
- 非常好的化学性能
- 不含卤素和镉
- 温度范围: -40°C 至 +105°C;
- 包装配件: 法兰主体, 固定夹 (包含两螺丝), 软管密封圈 (NVN3), 法兰密封圈 (FG04 或 FG04 / 01)
- 如应用温度高于70°C, 我们推荐使用附件, 软管内套支撑 (BES), 维持长时间的密封性能。